

# Series 210

Momentary Action Sealed Foot Switch Very low profile control with a polished aluminum housing 15 AMP, ½ HP, 125/250 VAC







## **Momentary Action**

#### **Custom Foot Switches:**

The Series 210 can be provided with special nameplates, cord sets, plugs, strain reliefs, and other features that may be required for specific applications.

### FEATURES

- 1. Polished aluminum housing with plated steel pedals.
- 2. ½: NPTF connector hole standard for cable strain relief fittings. Other connector holes available on request.
- 3. No exterior sprints! Two torsion springs located inside foot switch.
- 4. Two mounting holes.
- 5. Capable of handling up to 12/3 cable or .50" O.D.
- 6. .187" x .020" quick connect terminals.
- 7. Wide target area for foot operation.
- 8. Long life snap switch.
- 9. #8 grounding screw is provided.
- 10. Skid-resistant elastomeric base pad.
- 11. UL listed to U.S. and Canadian safety standards.
- NEMA and IEC Ingress Protection (IP) rated.
- 13. Two pedal model has an integral barrier.
- 14. Low profile design.
- 15. Buna-N O-Ring and Buna-N gasket seals.
- Numerous cord strain reliefs available for your special requirements.

## BENEFITS

The Series 200 foot switch was designed to offer environmentally sealed protection without the bulk of most sealed foot switches in the market today. Its unique treadle design provides a wide target area of operation. For operations requiring separate control initiation, a dual treadle model is available with an integrated barrier discouraging both treadles from operating at the same time.



135 Park Road • Putnam, CT 06260 860-928-0567 • ConnTrol.com

- Made in the USA
- No Minimum Order
- Superior Durability and Lifespan
- Exceptional Lead Times and Delivery

WARNING: It is the responsibility of the user to determine the suitability of a foot switch for the intended use and to determine that it will comply with all Federal, State, and Local safety and health regulations.