



1. The 600 features a flexible strain relief option for up to 18/3 SVT cord for longer cable life.
2. High strength socket head hinge screws.
3. All threaded openings are extruded to provide extra thread engagement.
4. Stable platform, even on corners!
5. Long life snap switch.
6. #8 grounding screw is provided.
7. High quality, black E-Coat.
8. UL listed and recognized to US and Canadian standards.
9. Wide target area!
10. 2-stage options available.



UNLESS STATED, TOLERANCES ARE:

.XX +/- .015  
.XXX +/- .005

\*ALL DIMENSIONS ARE IN INCHES\*

DRAWING NUMBER

Series 600 Sales Drawing

WS600-001

THIS DOCUMENT IS THE PROPERTY OF CONNTROL INTERNATIONAL, INC. AND IS NOT TO BE DISCLOSED, REPRODUCED, IN WHOLE OR IN PART, OR USED FOR MANUFACTURE FOR ANYONE OTHER THAN CONNTROL INTERNATIONAL, INC. WITHOUT ITS WRITTEN CONSENT.

APPROVED	JPB	8/14/2024
CHECKED	RB	8/14/2024
DRAWN	JPB	8/14/2024

MATERIAL	N/A	REV
SCALE	2:3	SIZE A
SHEET		1/1