

# Series 300

Variable, Momentary/Maintained Action  
Offers smooth operation with a durable  
aluminum or reinforced polycarbonate base



## FEATURES

1. Durable aluminum base with formed steel cover.
2. Ultra smooth variable speed operation.
3. 1/2" NPTF connector hole standard for cable strain relief fittings. Other connector holes available on request.
4. No exterior springs! Torsion springs located inside the foot switch.
5. Four mounting slots.
6. Capable of handling up to 12/3 cable or .50" O.D.
7. 10 amp, SPDT long life snap switch available to operate at beginning or end of stroke.
8. Equipped with 2 watt potentiometer (customer to specify Ohm rating and taper, i.e., linear or logarithmic).
9. #8 grounding screw is provided.
10. Skid-resistant elastomeric base pad.
11. Buna-N O-Ring and Buna-N gasket seals.
12. Numerous cord strain reliefs available for your special requirements.

## Maintained Action

### Custom Foot Switches:

The Series 300 can be provided with special nameplates, cord sets, plugs, strain reliefs, and other features that may be required for specific applications.

## BENEFITS

The Series 300 foot switch is engineered for operations that demand both precision and flexibility, providing ultra-smooth variable-speed control. Its durable construction and corrosion-resistant base ensure long-lasting performance, even in challenging environments.




**YOUR FOOT, OUR SWITCH**

135 Park Road • Putnam, CT 06260  
860-928-0567 • ConnTrol.com

- Made in the USA
- No Minimum Order
- Superior Durability and Lifespan
- Exceptional Lead Times and Delivery

WARNING: It is the responsibility of the user to determine the suitability of a foot switch for the intended use and to determine that it will comply with all Federal, State, and Local safety and health regulations.