


SCALE 1:2



1. Solid steel construction, with a full cover and base pads.
2. The 862 features a cable clamp that is located inside the foot switch.
3. Redundant corrosion-resistant spring system.
4. High strength socket head hinge screws.
5. All threaded openings are extruded to provide extra thread engagement.
6. Two mounting holes.
7. Capable of handling up to 14/3 cord.
8. .187" x .020" quick-connect terminals required.
9. Long life snap switch.
10. #8 grounding screw is provided.
11. High quality, black epoxy coating.



UNLESS STATED, TOLERANCES ARE:

.XX +/- .015
.XXX +/- .005

ALL DIMENSIONS ARE IN INCHES

DRAWING NUMBER

Series 862 Sales Drawing

WS862-001

THIS DOCUMENT IS THE PROPERTY OF CONNTROL INTERNATIONAL, INC. AND IS NOT TO BE DISCLOSED, REPRODUCED, IN WHOLE OR IN PART, OR USED FOR MANUFACTURE FOR ANYONE OTHER THAN CONNTROL INTERNATIONAL, INC. WITHOUT ITS WRITTEN CONSENT.

APPROVED JPB	8/14/2024	MATERIAL	N/A	REV
CHECKED RB	8/14/2024			
DRAWN JPB	8/14/2024	SCALE 2:3	SIZE A	SHEET 1/1