



MOUNTING SCREWS (X4)

CABLE CLAMP SCREWS (X2)

1. The Series 892 Dual is equipped with a protective foot guard.
2. Solid steel construction throughout, with a full cover and base pads.
3. Features a cable clamp and wire cover that are located at the rear of the guard.
4. Redundant corrosion-resistant spring system.
4. High strength socket head hinge screws.
5. All threaded openings are extruded to provide extra thread engagement.
6. Capable of handling up to 14/3 cord.
7. Long life snap switches.
9. #8 grounding screws are provided.
10. High quality, black epoxy coating on bases.
11. Durable powder coating on the guard.



UNLESS STATED, TOLERANCES ARE:

.XX	+/- .015
.XXX	+/- .005

ALL DIMENSIONS ARE IN INCHES

DRAWING NUMBER

Series 892 Dual Sales Drawing

WS892-201

THIS DOCUMENT IS THE PROPERTY OF CONNTROL INTERNATIONAL, INC. AND IS NOT TO BE DISCLOSED, REPRODUCED, IN WHOLE OR IN PART, OR USED FOR MANUFACTURE FOR ANYONE OTHER THAN CONNTROL INTERNATIONAL, INC. WITHOUT ITS WRITTEN CONSENT.

APPROVED	JPB	8/29/2024
CHECKED	RB	8/29/2024
DRAWN	JPB	8/29/2024

MATERIAL	REV
SCALE 1:4	SIZE A
SHEET 1/1	

